



Product Name: DEXTÖR ATF DEXRON III

Application: Automatic Transmission Fluid

Quality: Fully synthetic

Recommended for: Automatic gearboxes of American cars Like GM (2005 and earlier), FORD (Mercon) , CHRYSLER and Asian cars as HYUNDAI, KIA, MITSUBISHI, TOYOTA or European cars BMW, CITROËN, FIAT, MB, PEUGEOT, RENAULT also for Allison heavy duty transmissions wide range of European heavy duty automatic transmissions.

Drain Interval: between 48,000 to 80,000 kilometers or as specified in the vehicle's owner's manual.

Product Overview

DEXTÖR ATF DEXRON III is a high-performance automatic transmission fluid (ATF) designed to meet the demands of modern and older transmissions. It ensures excellent friction stability, wear protection, and low-temperature fluidity for smooth and efficient operation under a wide range of conditions.

Application

Recommended for:

- Automatic transmissions requiring **Dexron® (except Dexron VI)** or **Mercon®** specifications.
- Vehicles from manufacturers such as GM, Ford, Chrysler, Toyota, Hyundai, BMW, Renault, and others.
- Power steering units, boats, and industrial hydraulic systems.
- Older automatic gearboxes and torque converters.

Performance Benefits

- **Thermal Stability:** Outstanding resistance to oxidation and heat, reducing deposits and extending fluid life.
- **Viscosity Stability:** High viscosity index ensures stable performance across a wide temperature range.
- **Corrosion Protection:** Prevents rust and corrosion, ensuring long component life.
- **Foam Resistance:** Anti-foam additives ensure consistent hydraulic performance.
- **Elastomer Compatibility:** Safe for synthetic rubber seals and gaskets.
- **Smooth Power Transmission:** Optimized friction characteristics deliver smooth shifting and efficient operation.
- **Wide Application Range:** Suitable for automatic gearboxes, torque converters, power steering units, and hydraulic systems

Meets and Approvals

- GM DEXRON IIIH, GM DEXRON IIIIG, GM DEXRON IIE, GM DEXRON IID, GM DEXRON II
- Ford MERCON
- Toyota ATF D-III
- Allison C-3, Allison C-4 , Allison TES 389
- VOLVO 97325 , VOLVO 97340
- ZF TE-ML 09 , ZF TE ML 05L , ZF TE ML 21L
- MAN 339 L1, MAN 339 V1, MAN 339 Z1





- MB-Approval 236.9
- Voith H55.6335.xx

Typical Properties

Property	Typical Value	Method
Color	Visual	Red
Density @ 15°C	ASTM D4052	0.847 g/cm ³
Kinematic Viscosity @ 40°C	ASTM D445	34.2 mm ² /s
Kinematic Viscosity @ 100°C	ASTM D445	7.4 mm ² /s
Viscosity Index	ASTM D2270	188
Pour Point	ASTM D97	-57°C
Flash Point	ASTM D92	216°C
Brookfield Viscosity @ -40°C	ASTM D2983	13097 mPa.s

Storage and Handling

Store in a cool, dry place away from direct sunlight. Ensure the product is sealed properly when not in use to maintain its performance characteristics.

Health and Safety

Refer to the Material Safety Data Sheet (MSDS) for detailed health and safety information. Handle used fluid responsibly to protect the environment.

