



**Product Name:** DEXTÖR ATF DEXRON VI

**Application:** Automatic Transmission Fluid

**Quality:** Fully synthetic

**Recommended for:** Automatic gearboxes, transfer case and power steering systems of American cars like GM (2006 and newer GM vehicles), FORD (Mercon), CHRYSLER, Asian cars as HONDA, HYUNDAI, KIA, ISUZU, MITSUBISHI, NISSAN, TOYOTA, or European cars, MERCEDES OPEL, Also use in older automatic gearboxes, torque converters, power steering, mechanical and hydraulic systems where DEXRON III H or DEXRON II D fluids are required.

**Drain Interval:** up to 150,000 km

---

## Product Overview

DEXTÖR ATF DEXRON VI is a 100% synthetic, low-viscosity, high-performance automatic transmission fluid engineered for modern automatic transmissions. Featuring advanced synthetic technology and powerful additives, it ensures exceptional aging and oxidation stability, smooth shifting under all conditions, and extended oil change intervals.

---

## Application

- Recommended for Automatic transmissions with or without slip lockup clutches.
- Transfer cases and power steering systems.
- Compatible with a broad range of American, Asian, and European vehicle manufacturers, including GM, Ford, Honda, Toyota, Hyundai, Mercedes-Benz, and others.
- Suitable for older transmissions requiring DEXRON III H or DEXRON II D fluids.

---

## Performance Benefits

- **Outstanding Friction Characteristics:** Enhances gear shifting performance and minimizes vibrations.
- **High Oxidation and Thermal Stability:** Prolongs transmission fluid life and prevents sludge/deposit formation.
- **Excellent Low-Temperature Performance:** Ensures reliable operation in extreme cold conditions.
- **Superior Wear Protection:** Extends the life of the transmission system.
- **Fuel Economy Benefits:** Reduces friction for better efficiency.
- **Anti-Foam and Corrosion Protection:** Maintains fluid integrity and safeguards system components.
- **Wide Compatibility:** Suitable for automatic gearboxes, power steering systems, and transfer cases

---

## Meets and Approvals

- **General Motors:** DEXRON VI
- **Ford:** MERCON LV, MERCON ULV
- **BMW:** M-1375.4, 83 22 0 142 516
- **Toyota:** WS
- **Mercedes-Benz:** MB 236.12, MB 236.14
- **Hyundai:** SP-IV, SP-IV-RR





- **Nissan:** Matic S, Matic P
- And many more (refer to full specifications).

## Typical Properties

Property	Typical Value	Unit	Method
Density @ 15°C	ASTM D 4052	g/cm <sup>3</sup>	0.8355
Viscosity @ 40°C	ASTM D445	mm <sup>2</sup> /s	30.12
Viscosity @ 100°C	ASTM D445	mm <sup>2</sup> /s	6.125
Viscosity Index	ASTM D2270	-	157
Brookfield Viscosity @ -40°C	ASTM D2983	mPa.s	9800
Pour Point	ASTM D97	°C	-51
Flash Point	ASTM D92	°C	222
Color	Visual	-	Red

## Storage and Handling

Store in a cool, dry place away from direct sunlight. Ensure the product is sealed properly when not in use to maintain its performance characteristics.

## Health and Safety

Refer to the Material Safety Data Sheet (MSDS) for detailed health and safety information. Handle used fluid responsibly to protect the environment.

