



**Product Name:** DEXTÖR ATF Mercon V

**Application:** Automatic Transmission Fluid

**Quality:** Fully synthetic

**Recommended for:** All vehicles of Ford requiring MERCON V quality fluids also Allison Power shift transmissions or other torque converters requiring Allison C-4 quality fluids.

**Drain Interval:** up to 150,000 km

---

## Product Overview

**DEXTÖR ATF Mercon V** is a high-quality automatic transmission fluid designed to meet the stringent requirements of Ford vehicles and other applications requiring MERCON V quality fluids. It is formulated with advanced synthetic base oils and performance-enhancing additives to provide exceptional thermal and oxidative stability, smooth shifting, and superior wear protection.

---

## Application

- Recommended for Ford automatic transmissions requiring MERCON V or MERCON quality fluids.
- Suitable for various automatic transmissions, including those from manufacturers such as Aisin Warner, Audi, BMW, Chrysler, Daimler, Nissan, Toyota, and more.
- Not recommended for use in Continuously Variable Transmissions (CVT), Dual Clutch Transmissions (DCT), or specific systems requiring MERCON SP or Type F fluids.

---

## Performance Benefits

- **Enhanced Durability:** Ensures superior transmission life and promotes smooth shifting.
- **Thermal Stability:** Exceptional protection against high temperatures and oxidation.
- **Cold Weather Performance:** Improved low-temperature fluidity for smooth operation in extreme conditions.
- **Rust and Corrosion Protection:** Guards components against wear and deterioration.
- **Seal Compatibility:** Superior seal compatibility for longer seal life and reduced leakage.
- **Foam Control:** Ensures a smooth and consistent shifting feel

---

## Meets and Approvals

### Approvals:

- Ford MERCON V
- Allison C-4
- JASO 1-A

### OEM Approvals :

- Aisin Warner: JWS 3309
- Audi: G 052 025-A2, G-052-162-A1
- BMW: LT 71141, ETL-8072B
- Chrysler: ATF +3, ATF +4
- Daimler: MB 236.1 to MB 236.11
- Nissan: Matic-D, J, K
- Toyota: T-III, T-IV
- General Motors: DEXRON, DEXRON-II, DEXRON-III





- Volkswagen: VW G 052 025-A2
- And many more.

## Typical Properties

Property	Typical Value	Method
Appearance	Visual	Clear & Bright
Viscosity @ 100°C, cSt	ASTM D445	7.216
Viscosity Index	ASTM D2270	180
Flash Point, °C	ASTM D92	220
Pour Point, °C	ASTM D97	-51
Brookfield Viscosity @ -40°C, cP	ASTM D2983	11,500
Density @ 15°C, Kg/L	ASTM D1298	0.8451

## Storage and Handling

Store in a cool, dry place away from direct sunlight. Ensure the product is sealed properly when not in use to maintain its performance characteristics.

## Health and Safety

Refer to the Material Safety Data Sheet (MSDS) for detailed health and safety information. Handle used fluid responsibly to protect the environment.

