



Product Name: DEXTÖR ATF SP-III

Application: Automatic Transmission Fluid

Quality: Fully synthetic

Recommended for: MITSUBISHI, HYUNDAI, KIA, and other 4-5 speed automatic transmissions where SP-III fluid is required, it replaces previous generation fluids: SP and SP-II Fluid

Drain Interval: 60,000 to 100,000 km

Product Overview

DEXTÖR ATF SP III is a high-performance synthetic automatic transmission fluid engineered to exceed the service fill requirements of MITSUBISHI, HYUNDAI, and KIA vehicles equipped with 4-5 speed automatic transmissions requiring SP III fluid. Its advanced formulation ensures effective wear protection, optimal friction characteristics, and exceptional thermal-oxidative stability to extend transmission lifespan and enhance driving comfort.

Application

- Recommended for MITSUBISHI, HYUNDAI, KIA, and other vehicles requiring SP III automatic transmission fluid.
- Backward compatible with SP and SP-II fluids.
- Suitable for use in power steering, hydraulic systems, and some manual transmissions where automatic transmission fluid is specified

Performance Benefits

- **Smooth Gear Shifts:** Anti-shudder performance ensures vibration-free, seamless driving.
- **Extended Transmission Life:** Superior wear protection, anti-sludge, and anti-corrosion properties.
- **Enhanced Stability:** Resistance to oxidation and thermal degradation for consistent performance.
- **Fuel Efficiency:** Optimized friction characteristics for efficient power transfer.
- **All-Weather Reliability:** Maintains performance in extreme temperatures, from -45°C to high summer heat.

Meets and Approvals

- MITSUBISHI Diaqueen SP-III, SP-II, SP
- HYUNDAI ATF RED-1K, JWS 3314, SP-III
- KIA ATF RED-1K, JWS 3314, SP-III
- TOYOTA DII/DIII, T-IV
- HONDA ATF Z-1 (excluding CVTs)
- NISSAN Matic C/D/J
- MAZDA ATF M-III/M-V
- ISUZU BESCO ATF-II, ATF-III
- many more





Typical Properties

Property	Typical Value	Unit	Method
Kinematic Viscosity @ 40°C	cSt	34.79	ASTM D445
Kinematic Viscosity @ 100°C	cSt	7.241	ASTM D445
Viscosity Index	-	179	ASTM D2270
Flash Point	°C	224	ASTM D92
Pour Point	°C	-48	ASTM D6892
Density @ 30°C	kg/L	0.8351	ASTM D4052
Color	-	Red	ASTM D1500

Storage and Handling

Store in a cool, dry place away from direct sunlight. Ensure the product is sealed properly when not in use to maintain its performance characteristics.

Health and Safety

Refer to the Material Safety Data Sheet (MSDS) for detailed health and safety information. Handle used fluid responsibly to protect the environment.

