



Product Name: DEXTÖR ATF WS

Application: Automatic Transmission Fluid

Quality: Fully synthetic

Recommended for: 2004 and above TOYOTA, LEXUS, VOLVO, and other 6 speed AISIN-WARNER automatic transmission systems where WS is required also, for use in many TOYOTA & LEXUS hybrid CVT cars

Drain Interval: 60,000 to 100,000 km

Product Overview

DEXTÖR ATF WS is a high-performance, fully synthetic, low-viscosity fluid tailored for automatic transmissions with or without slip-controlled lock-up clutch systems. Specially engineered for 6-speed TOYOTA and LEXUS vehicles equipped with AISIN-WARNER automatic transmissions, this fluid ensures optimal fuel economy and long-lasting performance. It is suitable for applications requiring WS fluid and provides superior wear protection, smooth gear shifts, and thermal stability.

Application

- Recommended for 2004 and newer TOYOTA, LEXUS, VOLVO, and other AISIN-WARNER automatic transmissions requiring WS fluid.
- Suitable for use in hybrid TOYOTA & LEXUS CVT systems.
- Not backward compatible with ATF Type T-IV or DEXRON fluids

Performance Benefits

- **Fuel Economy:** Reduces friction for optimized fuel efficiency, even at low temperatures.
- **Extended Protection:** Enhances wear protection, thermal stability, and oxidation resistance for prolonged transmission life.
- **Smoother Shifts:** Superior friction properties ensure smooth and seamless gear transitions.
- **Optimized Drain Intervals:** Effectively resists sludge, varnish, and deposit formation, extending fluid life and minimizing maintenance costs.

Meets and Approvals

- AISIN WARNER JWS 3324 ATF, ATF-0WS
- TOYOTA ATF WS (08886-02303, 08886-02305, 08886-80803)
- LEXUS ATF WS Lifetime
- VOLVO 1161540
- VW/AUDI G 055 025 A2
- and many more

Typical Properties

Property	Typical Value	Method
Kinematic Viscosity @ 40°C	ASTM D445	23.45cSt





Kinematic Viscosity @ 100°C	ASTM D445	5.345 cSt
Viscosity Index	ASTM D2270	173
Density @ 15°C	ASTM D4052	0.8345 g/cm ³
Flash Point	ASTM D92	220 °C
Pour Point	ASTM D97	-48°C
Brookfield Viscosity @ -40°C	ASTM D2983	7900 mPa·s
Color	Visual	Red

Storage and Handling

Store in a cool, dry place away from direct sunlight. Ensure the product is sealed properly when not in use to maintain its performance characteristics.

Health and Safety

Refer to the Material Safety Data Sheet (MSDS) for detailed health and safety information. Handle used fluid responsibly to protect the environment.

