



Product Name: DEXTÖR CVT FE

Application: Continuously Variable Transmission

Quality: Fully synthetic

Recommended for: Refill of pulley-based continuously variable transmissions in Japanese designed vehicles, except for toroidal CVTs and CVTs that require gear oils.

Drain Interval: 80,000-100,000 km (50,000–62,000 miles) or every 5–6 years.

Product Overview

DEXTÖR CVT FE is a premium-quality, fully synthetic transmission fluid designed for the latest-generation CVTs, particularly those requiring energy-efficient, low-viscosity fluids. Engineered with advanced synthetic base oils and cutting-edge additives, it ensures exceptional thermal stability, anti-vibration properties, and superior frictional performance.

Application

- Specifically formulated for modern belt- and pulley-type CVTs requiring low-viscosity fluids.
- Compatible with TOYOTA CVTF FE and other specifications requiring high performance and durability.
- Not recommended for chain-type CVTs or applications that require higher-viscosity or gear oils

Performance Benefits

- **Fuel Efficiency:** Lower viscosity reduces drag and improves transmission efficiency, contributing to better fuel economy.
- **Smooth Shifting:** Optimized friction characteristics ensure seamless, step-less shifting and improved driving comfort.
- **Extended Durability:** Advanced additive technology enhances thermal stability, oxidation resistance, and wear protection, prolonging CVT life.
- **Low-Temperature Performance:** Exceptional fluidity at sub-zero temperatures ensures smooth start-ups and reliable lubrication in cold conditions.
- **Seal Compatibility:** Prevents leaks by ensuring compatibility with common seal materials

Meets and Approvals

- TOYOTA CVTF FE
- HONDA HCF-2
- SUBARU Lineartronic CVTF
- MITSUBISHI DiaQueen CVTF-J4
- SUZUKI CVT Green 2
- DAIHATSU Amix CVTF FE
- MAZDA CVTF 3320

Typical Properties

Property	Method	Typical Value
----------	--------	---------------





Density @ 15°C (g/cm ³)	ASTM D-4052	0.8388
Flash Point (°C)	ASTM D-92	220
Pour Point (°C)	ASTM D-97	-51
Kinematic Viscosity @ 40°C (cSt)	ASTM D-445	23.44
Kinematic Viscosity @ 100°C (cSt)	ASTM D-445	5.562
Viscosity Index	ASTM D-2270	190
Color	Visual	Neutral

Storage and Handling

Store in a cool, dry place away from direct sunlight. Ensure the product is sealed properly when not in use to maintain its performance characteristics.

Health and Safety

Refer to the Material Safety Data Sheet (MSDS) for detailed health and safety information. Handle used fluid responsibly to protect the environment.

