



**Product Name:** DEXTÖR CVT SB-II

**Application:** Continuously Variable Transmission

**Quality:** Fully synthetic

**Recommended for:** SUBARU CVT gearbox type, model year 2015 onwards. Not recommended for CVT unit fitted in hybrid vehicles.

**Drain Interval:** 60,000 to 100,000 Km.

## Product Overview

**DEXTÖR CVT SB-II** is a high-performance Technosynthese transmission fluid designed specifically for Subaru Lineartronic CVT gearboxes (2015 models onward). This premium fluid provides exceptional power transfer, smooth driving performance, and superior fuel efficiency while ensuring long-lasting durability and optimal protection.

## Application

Recommended for:

- Designed for Subaru Lineartronic CVT systems, equivalent to Subaru CVT Fluid Lineartronic No. 2 (K0425Y0711).
- Not recommended for hybrid CVT units or automatic transmissions other than CVTs

## Performance Benefits

- **Anti-Shudder Performance:** Ensures smooth, seamless shifting and enhanced driving comfort.
- **Fuel Efficiency:** Optimized to maximize torque and horsepower output for better mileage.
- **Thermal and Oxidation Stability:** Extends fluid life under extreme operating conditions.
- **Wear Protection:** Prevents wear on belts, chains, and pulleys, ensuring long-lasting transmission health.
- **Low-Temperature Performance:** Excellent flow properties for reliable cold-weather operation.
- **Seal Compatibility:** Protects seals from shrinkage, hardening, or cracking to prevent leaks

## Meets and Approvals

- SUBARU CVT FLUID

## Typical Properties

Property	Unit	Method	Typical Value
Color	-	Visual	Green
Density @ 15°C	g/cm <sup>3</sup>	ASTM D4052	0.8345
Kinematic Viscosity @ 40°C	mm <sup>2</sup> /s	ASTM D445	34.09
Kinematic Viscosity @ 100°C	mm <sup>2</sup> /s	ASTM D445	7.258
Viscosity Index	-	ASTM D2270	185
Brook Field Viscosity @ -40°C	mPa.s	ASTM D2983	7890
Flash Point	°C	ASTM D92	218





Foam, Seq I @ 24°C	ml-ml	ASTM D892	0-0
Foam, Seq II @ 93.5°C	ml-ml	ASTM D892	0-0
Foam, Seq III @ 24°C	ml-ml	ASTM D892	0-0

## Storage and Handling

Store in a cool, dry place away from direct sunlight. Ensure the product is sealed properly when not in use to maintain its performance characteristics.

## Health and Safety

Refer to the Material Safety Data Sheet (MSDS) for detailed health and safety information. Handle used fluid responsibly to protect the environment.

