



Product Name: DEXTÖR CVT TC

Application: Continuously Variable Transmission

Quality: Fully synthetic

Recommended for: TOYOTA CVTF TC and vehicles featuring SUPER CVT-i technology **also** passenger cars and light-duty trucks where CVTF TC fluids are specified.

Drain Interval: 60,000-80,000 km or approximately every 4–5 years.

Product Overview

DEXTÖR CVT TC is a high-quality synthetic transmission fluid, specially formulated for belt-driven continuously variable transmissions (CVTs) in passenger cars. Engineered to deliver superior performance and reliability, it provides optimal frictional properties, excellent thermal stability, and long-lasting protection for modern CVT systems.

Application

DEXTÖR CVT TC is compatible with belt-driven CVTs and recommended for:

- Vehicles requiring TOYOTA CVTF TC or equivalent specifications.
- Cars with SUPER CVT-i systems.

Note: Not suitable for Nissan Extroid CVTs or automatic transmissions (ATs). Always consult the vehicle's owner's manual for proper application

Performance Benefits

- **Superior Anti-Judder Performance:** Enhances driving comfort and reliability by reducing vibration and ensuring smooth operation.
- **Thermal and Oxidation Stability:** Maintains consistent performance under high-temperature conditions, preventing sludge and varnish formation.
- **Excellent Wear Protection:** Protects against wear, rust, and corrosion, extending the life of CVT components.
- **High Power-Transmission Efficiency:** Ensures reliable torque transfer and smooth shifting for a comfortable driving experience.
- **Outstanding Low-Temperature Fluidity:** Improves transmission efficiency and startability in cold conditions.
- **Seal Compatibility and Foam Resistance:** Prevents leakage and ensures stable performance under demanding conditions

Meets and Approvals

- TOYOTA CVTF FE
- HONDA HCF-2
- SUBARU Lineartronic CVTF
- MITSUBISHI DiaQueen CVTF-J4
- SUZUKI CVT Green 2
- DAIHATSU Amix CVTF FE
- MAZDA CVTF 3320





Typical Properties

Property	Method	Typical Value
Appearance	ASTM D4176	B & C
Color	ASTM D1500	Red
Density @ 30°C (g/cm ³)	ASTM D4052	0.8356
Kinematic Viscosity @ 40°C (cSt)	ASTM D445	33.17
Kinematic Viscosity @ 100°C (cSt)	ASTM D445	7.219
Viscosity Index	ASTM D2270	186
Flash Point (°C)	ASTM D92	220
Pour Point (°C)	ASTM D97	-51

Storage and Handling

Store in a cool, dry place away from direct sunlight. Ensure the product is sealed properly when not in use to maintain its performance characteristics.

Health and Safety

Refer to the Material Safety Data Sheet (MSDS) for detailed health and safety information. Handle used fluid responsibly to protect the environment.

