



Product Name: DEXTÖR DCT Fluid

Application: Dual clutch transmission fluid

Quality: Fully synthetic

Recommended for: Wide variety of North American, European, and Asian vehicles equipped with wet dual clutch transmissions (DCT) like : Audi BMW, Citroen Ford / Getrag, Mitsubishi, Peugeot, Porsche (ZF transmission), Skoda, Volvo cars, VW.

Drain Interval: 40,000 to 60,000 km

Product Overview

DEXTÖR DCT Fluid is a high-performance, full synthetic lubricant developed for modern wet dual-clutch transmissions (DCT). This advanced formula ensures exceptional durability, smooth operation, and compatibility across a wide range of North American, European, and Asian vehicles.

Application

DEXTÖR DCT Fluid is suitable for a wide range of wet DCT-equipped vehicles, including but not limited to:

- **German OEMs:** BMW, Volkswagen, Mercedes-Benz, Porsche, Smart.
- **Asian OEMs:** Mitsubishi, Hyundai, Nissan.
- **European OEMs:** Renault, Volvo, Citroën.

Not recommended for step automatic or continuously variable transmissions (CVTs)

Performance Benefits

- **Exceptional Oxidation Stability:** Maintains fluid integrity and prolongs transmission life.
- **Smooth Shifting Performance:** Optimized clutch friction durability for consistent performance.
- **Temperature Resilience:** Excellent viscosity stability across a broad temperature range, ensuring reliable lubrication in extreme conditions.
- **Wear Protection:** Provides robust protection against wear and tear under high stress.
- **Rust and Corrosion Resistance:** Prevents damage to critical transmission components.
- **Seal Compatibility:** Prevents leaks and enhances fluid reliability.

Meets and Approvals

- **BMW:** DCTF-1, DCTF-2, 83 22 2 148 578, 83 22 2 148 579
- **Ford:** WSS-M2C936-A, Powershift
- **Mercedes-Benz:** MB 236.21, 236.24
- **Volkswagen:** TL 52182, TL 52529
- **Porsche:** 999.917.080.00
- **Volvo:** 1161838, 1161839
- **many more**





Typical Properties

Property	Typical Value	Method
Density @ 15°C (g/cm ³)	ISO 3675	0.8365
Kinematic Viscosity @ 40°C (mm ² /s)	ISO 3104	36.46
Kinematic Viscosity @ 100°C (mm ² /s)	ISO 3104	7.453
Viscosity Index	ISO 2909	177
Pour Point (°C)	ISO 3016	-51
Flash Point (°C)	ISO 2592	218
Color	Visual	Light Amber/Red

Storage and Handling

Store in a cool, dry place away from direct sunlight. Ensure the product is sealed properly when not in use to maintain its performance characteristics.

Health and Safety

Refer to the Material Safety Data Sheet (MSDS) for detailed health and safety information. Handle used fluid responsibly to protect the environment.

