



Product Name: DEXTÖR DSG

Application: Dual Clutch Transmissions

Quality: Fully synthetic

Recommended for: The DSG (Direct Shift Gearbox) of VAG (Volkswagen, Audi, Seat, Skoda), this fluid can also be used for other 6-speed DCT transmissions, such as Chrysler Powershift, Ford Powershift, Mitsubishi TC-SST, Volvo Powershift, BMW Drivelogic 7-speed, etc.

Drain Interval: 40,000 to 60,000 km

Product Overview

DEXTÖR DSG Fluid is a high-performance full synthetic lubricant engineered with superior quality base oils and advanced additive technology. It is specifically formulated for modern Dual Clutch Transmission (DCT) systems to ensure reliable performance, extended gearbox life, and smooth operation.

Application

This product is primarily designed for DSG (Direct Shift Gearboxes) used in vehicles from VAG (Volkswagen, Audi, Seat, Skoda) and is compatible with other DCT systems such as:

- **6-Speed DCT:** Chrysler Powershift, Ford Powershift, Mitsubishi TC-SST, Volvo Powershift
- **7-Speed DCT:** BMW Drivelogic and others

Note: Not suitable for VW dry clutch DSG types 0AM, 02M, 02Q, and 02S

Performance Benefits

- **Extended Gearbox Life:** Superior anti-wear and load-carrying properties.
- **Optimal Shifting Performance:** Maintains smooth and vibration-free operation.
- **Thermal Stability:** Resists oxidation and heat degradation for extended oil life.
- **Broad Compatibility:** Meets multiple OEM requirements for modern DCT systems.

Meets and Approvals

- **VAG:** G 052 182, G 052 529, G 055 529
- **BMW:** DCTF-1, MTF-LT-5, FFL-4
- **Ford:** WSS-M2C-936-A, WSS-M2C-200-D2
- **Volvo:** 1161838, 1161839
- **Other OEMs:** Porsche, Mercedes-Benz, Renault, PSA, Mitsubishi, and Bugatti

Typical Properties

Property	Typical Value	Unit	Method
Density at 15°C	DIN 51757	kg/m ³	847
Kinematic Viscosity at 40°C	DIN 51562	mm ² /s	36.0
Kinematic Viscosity at 100°C	DIN 51562	mm ² /s	7.0
Viscosity Index	DIN ISO 2909	-	158
Dynamic Viscosity at -40°C	DIN 51938	mPa.s	<18,000





Pour Point	DIN ISO 3016	°C	-45
Flash Point (COC)	DIN ISO 2592	°C	>200

Storage and Handling

Store in a cool, dry place away from direct sunlight. Ensure the product is sealed properly when not in use to maintain its performance characteristics.

Health and Safety

Refer to the Material Safety Data Sheet (MSDS) for detailed health and safety information. Handle used fluid responsibly to protect the environment.

