



Product Name: DEXTÖR Universal Synthetic ATF

Application: Automatic Transmission Fluid

Quality: Fully synthetic

Recommended for: Automatic transmissions made by manufacturers in North America, Europe, Asia, and other parts of the world like DEXRON VI, DEXRON III/III(H)/IIE, DEXRON II, MERCON LV, Hyundai/KIA SP-II/III/IV, Toyota WS/T-III/T-IV, Mercedes, Honda Z-1, Allison and Nissan Matic Fluids

Drain Interval: 100,000–160,000 km

Product Overview

DEXTÖR Universal Synthetic ATF is an advanced full synthetic automatic transmission fluid engineered to meet the demanding needs of modern transmissions. Designed as a versatile, universal fluid, it ensures optimal performance, smooth shifting, and superior wear protection across a broad range of OEM applications.

Application

DEXTÖR Universal Synthetic ATF is suitable for

- Passenger cars, SUVs, and light trucks.
- Power steering systems and hydraulic units where ATF is specified.
- Compatible with both high and low viscosity applications, ensuring reliability across a wide range of vehicle types.
- Not recommended for use in CVTs, DCTs, Ford Type F applications, or extended drain heavy-duty applications

Performance Benefits

- **Universal Application:** Consolidates inventories and reduces inventory investment.
- **Excellent Oxidation Stability:** Provides long-lasting high-temperature protection, minimizing sludge formation and wear.
- **High Shear Stability:** Maintains friction characteristics over extended service intervals and a wide temperature range.
- **Reduced Foaming:** Enhances smooth operation and prevents fluid degradation.
- **Improved Pitting Protection:** Offers increased durability for transmission components.

Meets and Approvals

Approvals :

- GM DEXRON®-VI, DEXRON®-III/III(H)/IIE/II
- Ford MERCON® LV
- Hyundai/KIA SP-II, SP-III, SP-IV
- Toyota WS, T-III, T-IV
- Honda ATF-Z1, DW-1
- Nissan MATIC-D/J/K/S
- Mercedes-Benz 236.1-236.9
- many more

Meets :





- Allison C-4
- ZF 5HP18FL, 5HP24, 8HP, 9HP
- JASO M315-2013 1A-LV
- BMW LA2634, LT71141
- many more

Typical Properties

Property	Typical Value	Method
Kinematic Viscosity @ 40°C	ASTM D-445	29.1 cSt
Kinematic Viscosity @ 100°C	ASTM D-445	5.9 cSt
Viscosity Index	ASTM D-2270	153
Brookfield Viscosity @ -40°C	ASTM D-2893	10,000 cP
Appearance	Visual	Red

Storage and Handling

- Store in a cool, dry place away from direct sunlight.
- Avoid contamination with other fluids.
- Follow proper disposal protocols for used fluid.

Health and Safety

Refer to the Material Safety Data Sheet (MSDS) for detailed health and safety information. Handle used fluid responsibly to protect the environment.

